



Manure Storage Design Opportunities

Jennifer L. Keuning, M.S.
Environmental Scientist
Conestoga-Rovers & Associates


CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services



Presentation Overview

- About CRA & CRA's Agricultural Services
- Design Requirements
- Design of Manure Storage Facilities
 - Construction Materials
 - Capacity & Configuration
 - Cost comparison
 - Management & Maintenance
- Safety Considerations


CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services



About CRA

- Conestoga-Rovers & Associates (CRA)
 - Established in 1976, providing engineering, environmental, construction, and information technology (IT) services
 - Current workforce of over 3,000 people in 90 offices
 - Provided services on 1,000s of projects in over 60 countries
 - Completed over 250 projects on farms across North America, including designs of manure storage facilities


CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services



CRA's Agricultural Services

- CRA's Agricultural Experience
 - Manure Storage System Evaluations and Designs completed on: Dairy 100+; Beef 20+; Swine 10+; Poultry 10+
 - Storage types including: earthen, synthetic, and concrete lined ponds; concrete tanks & dry stacks
 - Bedding and manure separation systems
 - Gravity and pumped transfer systems
 - Leachate collection and treatment systems

CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services



Design Requirements

- Must meet NRCS CPS-313 Waste Storage Facility standard
 - Soil profile including bedrock and groundwater location
 - Setbacks to features such as property lines, wells, wetlands, etc.
 - Material being stored in the waste storage facility
 - Planned storage period
 - Intended management style including waste handling and transfer methods
 - Provisions for facility expansion
 - Potential odor concerns

CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services



Design Requirements – CAFOs


- Must meet additional requirements of NR243
- 180 days of containment for liquid
 - Manure
 - Bedding
 - Parlor wastewater
 - Leachate and collected runoff from feed storage
 - Wastewater from other sites from lots, barnyards
 - Normal precipitation less evaporation on the surface of the facility
 - Runoff volumes from the drainage areas
 - 25-year, 24-hour precipitation on the surface of the facility
 - 25-year, 24-hour runoff volume from the drainage area
 - Solids accumulation
 - Freeboard (1-foot)

CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services




Construction Materials

- Compacted Clay Lined Lagoons
 - Can be >20 ft depth
 - Requires soils with greater than 50% fines and plasticity index greater than 12
 - 3 ft to 6 ft thick clay liner required based on depth
 - Material must be over excavated and re-compacted
 - Requires testing of liner material for compaction and permeability
 - Requires at least 4 ft separation to saturation and bedrock, increasing with depth of lagoon



CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services








Construction Materials



Construction Materials

- Geomembrane Lined Lagoons
 - 60 mil HDPE, LLDPE or EPDM material over secondary clay liner
 - Requires secondary clay liner of at least 2 ft thickness and greater than 40% fines
 - Requires 3rd party testing of liner material for material strength, seam strength & leakage
 - Requires greater than 4 ft separation to saturation and bedrock



CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services



CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services



CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services







Construction Materials

➤ Geosynthetic Clay Lined Lagoons

- Bentonite material encased in geotextiles
- Not very common in the area
- Self healing type of liner
- Requires secondary clay liner of at least 2 ft thickness and greater than 20% fines
- Requires liner cover material of 1 ft on the bottom and 2 ft on the sides
- Requires greater than 4 ft separation to saturation and bedrock



CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services

Construction Materials

➤ Concrete Lined Lagoons

- Two types approved: concrete with waterstop & concrete-soil composite
- Concrete with waterstop has no soil requirements and requires 2 ft separation to saturation and bedrock
- Concrete-soil composite has 4 sub criteria based on site conditions with minimum 3 ft separation to saturation and bedrock



CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services



CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services












Construction Materials

- Manure Storage Tanks
 - Constructed of concrete or steel
 - Concrete tanks can be partially below grade where steel tanks are all above grade
 - Waterstops at all joints for water tightness
 - Require 2 ft separation to saturation and bedrock
- Solids stacking pads
 - Constructed similar to concrete tanks with waterstop at all joints
 - Must contain 25-year, 24-hour storm event by sloping storage or collection system
 - Require 2 ft separation to saturation and bedrock

CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services







Design Considerations

➤ Cost Comparison of Liners

Material Type	Approximate Cost
Compacted Clay	\$7.00 to \$12.00 per yd ³
60 mil HDPE	\$0.70 to \$1.30 per ft ²
60 mil EPDM	\$1.00 to \$1.60 per ft ²
GCL Liner Cost vary greatly depending on location, design, size & complexity	\$1.00 to \$1.50 per ft ²
Concrete Liner	\$2.50 to \$4.50 per ft ²


CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services

Design Considerations

CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services

Site Characterization

CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services



Design Considerations


- Locating a Manure Storage
 - Preliminary size storage facility based on production numbers to estimate general footprint
 - Identify potential location for manure storage
 - Verify all setbacks from sensitive features
 - Identify soil conditions in proposed area
 - Start selection of liner type:
 - ✓ What management practices will be used?
 - ✓ Will sand bedding be used?
 - ✓ How will accumulated solids be removed?
 - ✓ Are site conditions suitable for this type of liner?
 - ✓ Will the design allow for future expansion?
 - ✓ What are the construction and maintenance costs?
 - Select liner and complete design

CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services



A site plan diagram showing a farm layout with various structures and a manure storage facility highlighted in green. The plan includes a central building, several smaller structures, and a large green rectangular area representing the manure storage. A road or path is shown at the bottom of the plan.

CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services



Design Considerations

- Additional Considerations
 - Additional storage capacity especially if using a flush flume system
 - Multiple smaller storages to allow better management and increased safety
 - Plan for growth of the farm when locating and sizing manure storages
 - Agitation techniques when choosing depth and size of manure storages
 - How wastewater will get to the facility and how it will be removed?
 - Predominant wind direction and odor potential
 - Where solids will settle in the storage system

CRAWORLD.COM Worldwide Engineering, Environmental, Construction, and IT Services












Design Considerations

- Cover Systems
 - Cover systems can be installed on all types of lagoons and tanks to reduce odor
 - Constructed typically of HDPE with drainage channels and floats
 - Requires rain water to be pumped off using pumps on the cover system
 - Gas is collected under the cover and can be flared, sent through a biofilter or tied into a digester system











Safety Considerations

- Safety Considerations
 - Emergency Response Plan
 - Maintenance of liner and berms
 - Rails and fencing
 - Exclusion of people, animals, and equipment
 - Confinement areas
 - Buildup of hazardous gases



The image shows a large body of water, likely a containment pond, with a concrete structure and a fence in the foreground. The water is blue, and the surrounding area is green with trees and grass. The image is framed with a green border and includes a small inset image in the top left corner. At the bottom, there is a logo for CRAWORLD.COM and the text "Worldwide Engineering, Environmental, Construction, and IT Services".

 **Summary**

- Design Standards
- Design of Manure Storage Facilities
 - Construction Materials
 - Capacity & Configuration
 - Cost comparison
 - Management & Maintenance
- Safety Considerations



 **CRAWORLD.COM** Worldwide Engineering, Environmental, Construction, and IT Services

 **Questions/Comments**

Jennifer Keuning, M.A.Sc.
Conestoga-Rovers & Associates
jkeuning@craworld.com
Tel: (920) 490-1663
Fax: (920) 490-1668





 **CRAWORLD.COM** Worldwide Engineering, Environmental, Construction, and IT Services
